STI F921 VERTICAL ABOVEGROUND DOUBLE WALL STORAGE TANKS

2* Min Monitor Opening Outi	EMERGENCY VENT OPENING (SECONDAR		EMERGENCY VENT OPENING (PRIMARY)	
OUTE		<u></u>		
	APPROX. CAPACITY (GALLONS)	NOM. DIAMETER	NOM. HEIGHT	
	560	48"	6'-0"	
	1,000	64"	6'-0"	
	2,000	64"	12'-0"	
	3,000	84"	10'-6"	
	3,000	96"	8'-0"	
	4,000	96"	10'-8"	
	6,000	96"	16'-0"	
	6,000	120"	10'-3"	
	8,000	120"	13'-8"	
	10,000	120"	17'-0"	
	12,000	120"	20'-6"	
	16,500	120"	28'-0"	
	15,000	126"	23'-2"	
	15,000	144"	17'-9"	
	20,000	144"	23'-8"	
	24,000	144"	29'-0"	
	29,600	144"	35'-0"	
	Tank lengths listed above	are based on nominal inr will vary during actual m		

STANDARD SPECIFICATIONS

modern

- Tank meets UL142 and F921standards for double wall design.
- Tanks bear the UL and F921 label for secondary containment.
- Modern's standard opening locations and required lifting lugs.
- Exclusive free flow annular space design.
- Exterior coated with one (1) coat of standard shop primer and not blast cleaned.
- Check with Modern for type of Emergency Vent Opening supplied.
- Other exterior and interior coating systems available upon request.
- Other tank sizes available upon request.